

BLANK PAGE



Indian Standard DIMENSIONS FOR STEEL TUBES FOR AUTOMOTIVE PURPOSES

(First Revision)

Third Reprint OCTOBER 1994

UDC 669.14-462:629.113:006.78

© Copyright 1979

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard DIMENSIONS FOR STEEL TUBES FOR AUTOMOTIVE PURPOSES

(First Revision)

Steel Tubes, Pipes and Fittings Sectional Committee, SMDC 22

Chairman

Representing

SHRI J. G. KESWANI

The Indian Seamless Metal Tubes Ltd. Bombay

Members

SHRI M. M. AERON

Steel Authority of India Ltd, Rourkela Steel Plant. Rourkela

SHRI R. N. TANDON (Alternate)

SHRIK, K. AHUJA

SHRI P. C. JOHARI (Alternate)

SHRI S. C. ANAND

SHRI M. P. MITTAL (Alternate)

Assistant Director Standards Ministry of Railways

(Loco), Lucknow SHRIS. N. BASU

Directorate General of Supplies Disposals

SHRI T. N. UBOVEJA (Alternate)

SHRI D. P. BHATTACHARJEE

SHRIS. C. ARORA (Alternate)

SHRI B. C. CHAKRABORTY

SHRI V. K. CHATURVEDI (Alternate)

SHRI B. B. CHARRAVERTI

SHRI L. M. CHAUDHRI

SHRI A. K. SHOME (Alternate)

SHRI K, K. GANDHI (Alternate)

SHRI JACOB JOHN SHRI A. K. MITRA (Alternate)

SHRI B. KUMAR

SHRI T. K. BASU (Alternate) SHRIK. MURHERJEE

SHRI R. K. SINHA (Alternate) SHRI P. T. SHANKARAN NAYAR

SHRI G. S. GOSAL (Alternate)

Indian Oil Corporation Ltd, Bombay

Bharat Steel Tubes Ltd. New Delhi

(Inspection Wing), New Delhi Export Inspection Council of India, Calcutta

Oil & Natural Gas Commission, Dehra Dun

Superintendence Co of India (P) Ltd, Calcutta

Public Works Department (Public Health Branch), Government of Haryana, Chandigarh

Kalinga Tubes Ltd, Calcutta

Stewarts & Lloyds of India Ltd, Calcutta

The Fertilizer Corporation of India Ltd. Sindri

Central Boilers Board, New Delhi

(Continued on page 2)

(c) Copyright 1979

BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 5429 - 1979

(Continued from page 1)

Members

Director (Struc & Met)

(Secretary)

Representing

Zenith Steel Pipes and Industries Ltd, Khopoli SHRIS, NEELAKANTAN DR A. R. KESKAR (Alternate) Indian Register of Shipping, Bombay SHRI V. N. PANDEY SHRI S. CHANDRA (Alternate) SHRI N. V. RAGHAVAN Indian Tube Co Ltd, Jamshedpur SHRI D. DUTTA (Alternate) Tube Products of India, Madras SHRIS, RANGANATHAN SHRI T. SIVASHANKAR (Alternate) SHRI M. C. KESAVA RAO Hindustan Shipyard Ltd. Visakhapatnam SHRI M. VEERABABU (Alternate) Bharat Heavy Electricals Ltd, Tiruchirapalli SHRI A. SRINIVASULU SHRI H. J. THAKAR SHRI C. R. RAMA RAO, Gujarat Steel Tubes Ltd. Ahmadabad Director General, ISI (Ex-officio Member)

Indian Standard DIMENSIONS FOR STEEL TUBES FOR AUTOMOTIVE PURPOSES

(First Revision)

O. FOREWORD

- 0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 26 February 1979, after the draft finalized by the Steel Tubes, Pipes and Fittings Sectional Committee had been approved by the Structural and Metals Division Council.
- 0.2 This standard was first published in 1969. On the basis of experience gained during these years, it has been decided to revise this standard.
- 0.3 Material specification and designations are covered in IS: 3074-1979*.
- 0.4 In the formulation of this standard, due weightage has been given to international co-ordination among the standards and practices prevailing in different countries in addition to relating it to the practices in the field in this country. This has been met by deriving assistance from the following publications:
 - ISO/R 336-1976 Plain end steel tubes, welded or seamless. General table of dimensions and masses per unit length. International Organization for Standardization.
 - BS 980: 1950 Steel tubes for automobile purposes. British Standards Institution.
- 0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960†. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

^{*}Specification for steel tubes for automotive purposes (first revision). †Rules for rounding off numerical values (revised).

IS: 5429 - 1979

1. SCOPE

- 1.1 This standard specifies dimensions of steel tubes used in automotives including scooters and motorcycles.
- 1.1.1 Outside diameters or thickness for shock absorber tubes are not specified in this standard. Purchasers are, however, recommended to ascertain from the manufacturers the sizes easily available before completing any design work which incorporates these tubes.

2. DIMENSIONS

- 2.1 The dimensions for steel tubes shall be as specified in Table 1.
- 2.1.1 Dimensions of tubes in this standard have been given in terms of outside diameter and the thickness of the tubes. Steel tubes for automotive purposes may also be ordered on the basis of inside diameter and thickness or to outside and inside diameters by special agreement between the purchaser and the manufacturer.
- 2.1.2 Dimensions of steel tubes specified in this standard are based on the usage of steel tubes in automobile industry. Requirement for the supply of steel tubes of special sizes, tolerances and finishes, etc, shall be subject to the agreement between the purchaser and the manufacturer.

3. TOLERANCES

3.1 Tolerance for Cold Drawn Seamless and Cold Drawn Electric Resistance Welded Steel Tubes — For cold drawn seamless (CDS) and cold drawn electric resistance welded steel tubes the following tolerances shall be permissible.

3.1.1 Tolerances on Thickness

- a) Tolerances on mean thickness No tube shall have a mean thickness that departs from the specified thickness by more than:
 - 1) ± 0.08 mm for tubes up to and including 2.0 mm thick,
 - ±0.1 mm for tubes above 2.0 mm thick up to and including 5.0 mm thick, and
 - 3) ± 2 percent for tubes over 5.0 mm thick.
- b) Maximum variation in thickness in any one tube At no point in the tube shall the variation in thickness be greater than ±10 percent of the actual mean thickness of the tube.
- 3.1.2 Tolerance on Mean Inside Diameter or Outside Diameter (Whichever is Specified) No tube shall have a mean inside or outside diameter that departs from the specified diameter by more than ± 0.1 mm for tubes up to and including 38.0 mm diameter, with the addition, for larger tubes, of ± 0.03 mm for each 13 mm or part thereof over 38.0 mm diameter.

TABLE 1 DIMENSIONS OF STEEL TUBES FOR AUTOMOTIVE PURPOSES (Clause 2.1)

Outside Diameter × Thickness mm × mm 10.2 × 0.6 10.2 × 1.0 10.2 × 1.6	mm × mm 31.8 × 1.0 31.8 × 1.6 31.8 × 3.2
12.0×0.6 12.0×1.2 12.0×1.6 12.0×2.3 13.5×2.0 16.0×1.2 16.0×1.6 16.0×2.6	38.0×1.2 38.0×1.6 38.0×2.0 38.0×2.6 38.0×4.0 38.0×6.3 44.5×1.0 44.5×1.6
16·0 × 3·2 17·2 × 1·6 17·2 × 2·0 20·0 × 2·0 20·0 × 2·6 20·0 × 3·2 22·2 × 1·6	44.5 × 2.3 44.5 × 3.2 44.5 × 5.9 51.0 × 1.2 51.0 × 1.6 51.0 × 2.6 51.0 × 5.9
22·2 × 2·0 22·2 × 2·6 22·2 × 3·2 22·2 × 4·0 25·4 × 1·6 25·4 × 2·3 25·4 × 3·2 25·4 × 3·2	57·0 × 1·6 57·0 × 5·0 63·5 × 1·6 63·5 × 2·6 63·5 × 4·0 63·5 × 6·3 70·0 × 2·9 76·2 × 2·6
25·4 × 4·0 30·0 × 2·0 30·0 × 3·2 30·0 × 4·0	76.2 × 4.0 76.2 × 5.6 88.9 × 3.2 101.6 × 4.5 101.6 × 10.0

3.1.3 Maximum Variation in Diameter in any One Tube — At no point in the tube shall the variation in outside diameter or inside diameter (whichever is specified) be greater than the value given below:

either

±0.05 mm greater than the tolerance on the mean diameter

01

$$\pm [0.13 \text{ mm} + \frac{D^3}{(1.000 t)^2}] \text{ mm, whichever is greater}$$

where

D = specified outside diameter of the tube in mm, and t = specified thickness of the tube in mm.

(The D^3 formula shall not apply to tubes where the D:t ratio is less than 40:1).

The limitations on extreme outside diameter or inside diameter are based on the specified diameter, that is, at no point in the tube shall the lowest reading of the diameter be less than the specified diameter minus the above tolerance, and the highest reading shall not be more than the specified diameter plus the above tolerance. The mean diameter shall be within the limits of the specified diameter plus and minus the tolerance on the mean diameter.

- 3.2 Tolerance for Electric Resistance Welded (ERW) Steel Tubes For electric resistance welded (ERW) steel tubes, tolerances on dimensions shall be as given below.
- 3.2.1 Tolerance on Thickness (Excluding Weld) ± 8 percent. The height of the internal fin shall be not greater than 60 percent of the specified wall thickness.
- 3.2.2 The internal welding bead shall be removed if so specified by the purchaser.

3.2.3 Tolerance on Mean Outside Diameter — The tolerance on mean outside diameter shall be as follows:

Outside Diameter of Tube		Tolerance
Over	Up to and Including	士
mm	mm	mm
-	25	0.10
25	51	0.13
51	63	0.18
63	7 6	0.20
76	88	0.25
88		0.30

3.2.4 Maximum Variation in Diameter in Any One Tube — At no point in the tube shall the variation in outside diameter greater than two values given below:

either ± 0.05 mm greater than the tolerance on the mean diameter

$$\pm [0.13 \text{ mm} + \frac{D^2}{(1.000 t)^2}] \text{ mm}$$
, whichever is greater

where

D = specified outside diameter of the tube in mm, and

t = specified thickness of the tube in mm.

(The D^2 formula shall not apply to tubes where the D:t ratio is less than 40:1).

The limitations on extreme outside diameter or inside diameter are based on the specified diameter, that is, at no point in the tube shall the lowest reading of the diameter be less than the specified diameter minus the tolerance, and the highest reading shall be not more than the specified diameter plus the tolerance on mean diameter.

Note — 'Mean' as used above is defined as half the sum of the maximum and minimum values.

BUREAU OF INDIAN STANDARDS

Headquarters:				
Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002				
Telephones: 331 01 31 Telegram	is : Manaksanstha			
331 13 75 (Comn	non to all Offices)			
Regional Offices :	Telephone			
Central : Manak Bhavan, 9, Bahadur Shah Zafar Marg.	∫331- 0 1 31			
NEW DELHI 110002	7 331 13 75			
Eastern : 1/14 C.I.T. Scheme VII M, V.I.P. Road, Maniktola, CALCUTTA 700054	37 86 62			
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	2 18 43			
Southern : C.I.T. Campus, IV Cross Road, MADRAS 600113	41 29 16			
Western : Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	6 32 92 95			
Branch Offices :				
'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMADABAD 380	001 2 63 48			
Peeriya Industrial Area, 1st Stage, Bangalore-Tumkur Road,	39 49 5 5			
BANGALORE 560058 Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. Nagar,	55 40 21			
BHOPAL 462003	33 40 21			
Plot No: 82/83, Lewis Road, BHUBANESHWAR 751002	5 36 27			
Kalai Kathir Building, 6/48-A Avanasi Road, COIMBATORE 64103	2 67 05			
Quality Marking Centre, N.H. IV, N.I.T., FARIDABAD 121001 Savitri Complex, 116 G. T. Road, GHAZIABAD 201001	8-71 19 96			
53/5 Ward No. 29, R.G. Barua Road, 5th By-lane,	3 31 77			
GUWAHATI 781003				
5-8-56C L. N. Gupta Marg, (Nampally Station Road) HYDERABAD 500001	23 10 83			
R14 Yudhister Marg, C Scheme, JAIPUR 302005 *	6 34 71			
117/418 B Sarvodaya Nagar, KANPUR 208005	21 68 76			
Plot No. A-9, House No. 561/63, Sindhu Nagar, Kanpur Road, LUCKNOW 226005	5 55 07			
Patliputra Industrial Estate, PATNA 800013	6 23 05			
District Industries Centre Complex, Bagh-e-Ali Maidan, SRINAGAR 190011				
T. C. No. 14/1421, University P. O., Palayam,	6 21 04			
THIRUVANANTHAPURAM 695034				
Inspection Offices (With Sale Point):				
Pushpanjali, First Floor, 205-A West High Court Road. Shankar Nagar Square, NAGPUR 440010	52 51 71			
Institution of Engineers (India) Building, 1332 Shivaji Nagar. PUNE 411005	5 24 35			
*Sales Office Calcutta is at 5 Chowringhee Approach, P. O. Princep Street, CALCUTTA	27 68 00			
† Sales Office is at Novelty Chambers, Grant Road, BOMBAY	89 65 28			
‡ Sales Office is at Unity Building, Narasimharaja Square, BANGALORE	22 39 71			

BANGALORE